

TRUCK MOUNTED PUMP



TECHNICAL HIGHLIGHTS

Energy Saving: Self-adaptive variable power distribution control technology

High-Efficiency: Good site adaptability (low side support)

High-Reliability: 8 years or 600,000 m³ without crack, making it equivalent to European standards.

Intelligence: Full self-diagnosis before, after and during pumping to ensure working safety.

Easy maintenance: Advanced easy-maintenance technologies, making maintenance time reduced by 50-75%.



36X-5Z

Maximum vertical reach	m	35.5
Maximum theoretical output	m ³ /h	120
Maximum theoretical pressure	bar	70



38X-5RZ (Two-Axles)

Maximum vertical reach	m	37.1
Maximum theoretical output	m ³ /h	100/100
Maximum theoretical pressure	bar	80/150

24X-4Z

Maximum vertical reach	m	23.2
Maximum theoretical output	m ³ /h	100/100
Maximum theoretical pressure	bar	60/100



32X-4Z

Maximum vertical reach	m	31.4
Maximum theoretical output	m ³ /h	120
Maximum theoretical pressure	bar	66



38X-5RZ (Three-Axles)

Maximum vertical reach	m	37.1
Maximum theoretical output	m ³ /h	100/100
Maximum theoretical pressure	bar	70/110